

TwistPort™ Shielded Adaptor V2 for Rocket M5

ADAPTOR FOR ROCKET™ M5

TwistPort™ Shielded Adaptor V2 introduces **wide frequency range of operation: 5180 - 6400 MHz!**

The TwistPort™ Shielded Adaptor V2 for Rocket M5 makes the Rocket™ M5 compatible with all TwistPort™ Antennas. TwistPort™ Adaptors are equipped with our original quick locking waveguide port. Connecting and disconnecting the Rocket™ M5 into the TwistPort™ Adaptor V2 is very simple and requires no tools.



TECHNICAL DATA

Antenna Connection	TwistPort™ - Quick Locking Waveguide Port
Radio Connection	2x Slide-On RP-SMA
Materials	Insert - Aluminium Alloy Shield - Aluminium Alloy and Zinc Alloy Adaptor - UV stabilized and weather resistant ABS plastic
Flame Rating	UL 94 HB
Temperature	-40°C to +60°C (-40°F to +140°F)
Wind Survival	160 km/h
Weight	0.5 Kg / 1.1 lbs – single unit 0.7 Kg / 1.5 lbs – single unit incl. package 15 Kg / 33 lbs – carton (20 units)
Single Unit	Retail Box: 24.3 × 11.7 × 11.7 cm
20 Units	Carton Box: 62 × 25 × 52 cm

PERFORMANCE

Frequency Range	5180 - 6400 MHz
Polarization	Dual Linear H + V
VSWR Max	1.8
Impedance	50 Ohm

COMPATIBLE WIRELESS PLATFORMS

RF elements®	any TwistPort™ Antenna
Ubiquiti Networks™	Rocket™ M5

PACKAGE CONTENTS

- TwistPort™ Adaptor Body
- TwistPort™ Adaptor Bottom Cover
- Screw 2.9 x 6.5 mm (2 pcs)

PRODUCT DIMENSIONS

