

02. HD-TVI CAMERA > 1080P CAMERA



HAC314-OD

IVMS HD-TVI 1080P Exterior IR Dome Camera

Features

- HD1080P Video Output
- Adopt HDTV Technology
- OSD menu, DNR
- 60 ft IR distance
- IP66 weatherproof
- Up the Coax(via coaxial cable)
- Optional UTP Balun available up to 600ft

Specification

| | |
|--------------------------------|---|
| Description | IVMS HD-TVI 1080P Exterior IR Dome Camera |
| Image sensor | 1 / 2,7in Progressive Scan CMOS |
| Signal system | PAL / NTSC |
| Effective pixels | 1930(H)*1088(V) |
| Min. illumination | 0.1 Lux @ (F1.2, AGC ON), 0 Lux with IR |
| Shutter time | 1/30s to 1/50,000 s |
| Lens | 3.6mm (2.8mm, 6mm optional), Angle of View: 80.9 degrees (3.6mm), 103.5 degrees (2.8mm), 54.3 degrees (6mm) |
| Angle adjustment | Pan: 0 - 360 degrees, Tilt: 0 - 90 degrees, Rotation: 0 - 360 degrees |
| Day & night | ICR |
| Video frame rate | 1080p @ 30fps |
| HD video output | 1 HD-TVI output up to 1200ft with RG59U 95% |
| CVBS Output | N/A |
| Privacy mask | On / Off, maximum 2 zones |
| Motion detection | On / Off, maximum 4 zones |
| Functions | Digital noise reduction, Digital zoom(62x) |
| Working Temperature / Humidity | -40 degrees C - 60 degrees C (-40 degrees F - 140 degrees F) Humidity 90% or less (non-condensing) |

| | |
|-----------------------|---------------------------|
| Power supply | 12 VDC+/-10% |
| Power consumption | Max. 3W |
| Weather proof ratings | IP66, IK10 |
| IR range | Up to 60 ft |
| Communication | OSD (UTC Control) via DVR |
| Dimensions | 4.37inx3.24in |
| Weight | 1.21lbs |