



**ES-5323**

**2 MEGAPIXEL BULLET IP CAMERA**

Features

- 2 megapixel (1600 x 1200) high resolution
- Real-time video recording
- True day / night
- IP66 rating
- IR range: up to 100ft

Specification

Image Sensor	1/3 inch Progressive Scan CMOS
Min. Illumination	0.5 lux@F1.2, AGC on, 0.1 lux@F1.2, AGC on, sens-up 5, 0 lux with IR
Shutter time	1/25s~1/100,000s
Lens	2.7 ~ 9mm @F1.2
Lens Mount	?14
Auto Iris	DC drive
Day& Night	IR cut filter with auto switch
Video Compression	H.264 / MPEG4 / MJPEG
Bit Rate	32 Kbps ~ 16 Mbps
Dual Stream	Yes
Max. Image Resolution	1600 x 1200
Frame Rate	15 fps (1600 x 1200) 25 fps (1280 x 960) 30 fps (1280 x 720)
Image Settings	Saturation, brightness, contrast adjustable through client software or web browser
Network Storage	NAS (iSCSI optional)
Alarm Trigger	Motion detection, tampering alarm, network disconnect , IP address conflict, storage exception
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, PPPoE, SMTP, NTP(SNMP, HTTPS, FTP, SIP, SRTP, 802.1x, IPv6 optional)

Security	User authentication, watermark
Communication Interface	1 RJ45 10M / 100M ethernet interface
Operating Conditions	-10 degree Celsius ~ 60 degree Celsius (14 degrees Fahrenheit ~ 140 degrees Fahrenheit) Humidity 90% or less (non-condensing)
Power Supply	12 VDC 10%, PoE (802.3af)
Power Consumption	Max. 9.5W
Weather Proof	IP66
IR Range	100ft
Dimensions	98 x 88.58 x 328.79 mm (3.86 inch x 3.49 inch x 12.94 inch)
Weight	1700 g (3.75 lbs)