

NETWORK VIDEO RECORDER > NVR



**ES-7604-P4**

## 4 CHANNEL PROFESSIONAL LEVEL IP NVR

Features

- Simultaneous HDMI, VGA, and CVBS output
- H.264 Compression Technology
- Intuitive Graphic User Interface
- Quick Search, Easy Backup
- Remote Monitoring / Control via CMS or Web Browsers
- Multi-User management
- Live View on Smart Phones and Playback on iPhones
- 3 Year Warranty & Free Life-Time Technical Support

Specification

|                       |                                                                                                   |
|-----------------------|---------------------------------------------------------------------------------------------------|
| Compression Format    | H.264                                                                                             |
| OS                    | Embedded Linux                                                                                    |
| IP Input              | 4CH, Max 20Mbps Input                                                                             |
| VGA Output            | 1 CH Resolution:<br>1920X1080P/60Hz,1600X1200/60Hz,1280X1024/60Hz,1280X720/60Hz,<br>1024X768/60Hz |
| CVBS                  | -                                                                                                 |
| HDMI Output           | 1 CH Resolution:<br>1920X1080P/60Hz,1600X1200/60Hz,1280X1024/60Hz,1280X720/60Hz,<br>1024X768/60Hz |
| Recording Resolution  | 5MP /3MP / 1080P / UXGA / 720P / D1 / VGA / DCIF / 2CIF / CIF / QCIF                              |
| Simultaneous Playback | 4CH D1 (Real-time), 4CH 720P, 2CH 1080P                                                           |
| Playback Resolution   | 5MP /3MP / 1080P / UXGA / 720P / D1 / VGA / DCIF / 2CIF / CIF / QCIF                              |
| Audio Input           | 1CH                                                                                               |
| Audio Output          | 1CH                                                                                               |
| SATA                  | 2 SATA Interfaces for 2 HDDs                                                                      |
| eSATA                 | -                                                                                                 |
| Capacity              | up to 4TB Capacity per Hard Drive                                                                 |
| Network Interface     | 1 RJ45 10M/100M/1000M adaptive Ethernet 4 independent 10/100 Mbps PoE Ethernet                    |

|                       |                                              |
|-----------------------|----------------------------------------------|
| USB Interface         | 2x USB 2.0                                   |
| Serial Interface      | 1xRS-485                                     |
| Alarm Input           | -                                            |
| Alarm Output          | -                                            |
| Mobile App            | Guardian Expert for iPhone/iPad/Android      |
| Consumption           | 15 W (without hard disk)                     |
| Power Supply          | 100VAC ~ 240VAC                              |
| Operating Temperature | -10 degree Celsius ~55 degree Celsius        |
| Humidity              | 10% ~ 90% Humidity                           |
| Chassis               | 19-inch rack-mounted 1U chassis              |
| Dimension             | 17.5 inch x 11.4 inch x 1.8 inch (W x D x H) |
| Weight                | 2 Kg ( without hard disk)                    |