

**Features:**

High power handling 6.5" in-ceiling speaker system  
Trimless magnetic grille  
Smooth-wide frequency response  
6.5 inch polypropylene woofer cone  
Rubber woofer surround  
20 oz ferrite woofer magnet  
1 inch aim-able silk dome tweeter  
Neodymium tweeter magnet  
High quality crossover with air core inductor  
Pure white acoustically lined grille .  
4 heavy duty mounting clamps.  
Gold plated 12awg binding posts  
Complete rough in bracket included (RI-675)  
Also available in 25/70 volt (E-675X, X20, X30)  
Sold as each  
Master carton 6 pcs  
10 year warranty



**Specifications:**

Diameter Woofer 6.5" (165.1mm) polypropylene  
Diameter Tweeter 1" (25.4mm) silk dome aim-able  
Power Handling 125 watts (peak)  
Impedance 8 ohms (nominal)  
Frequency Response 40Hz - 20kHz (±10dB)  
Dispersion 110 °  
Sensitivity 92dB (1W 1M) Average

**Included:**

RI-675 rough-in bracket  
Cutout template  
Paint shield  
Installation manual

**Dimensions:**

Dimensions Overall 9.125" (233mm)  
Cutout Dimensions Speaker 7.7" (196mm)  
Cutout Dimensions RI Bracket 8.1" (208mm)  
Depth 3- 1/4" (95.25mm)  
Shipping Weight 5.50 lbs (2.4kg)

