


Features:


High power handling 6.5" in-ceiling speaker system
 New magnetic trimless grille
 Smooth-wide frequency response
 6.5 inch polypropylene woofer cone
 Rubber woofer surround
 20 oz ferrite woofer magnet
 1 inch aim-able silk dome tweeter
 Neodymium tweeter magnet
 High quality crossover with air core inductor
 Pure white acoustically lined magnetic grille
 4 heavy duty mounting clamps.
 Gold plated 12awg binding posts
 Complete rough in bracket included (RI-675)
 Available in three 25/70V transformer options
 10 watt / 20 watt / 30 watt
 Sold as each
 Master carton 6 pcs
 10 year warranty



E-675TL-X
10 watt



E-675TL-X20
20 watt



E-675TL-X30
30 watt



Specifications:

Diameter Woofer 6.5" (165.1mm) polypropylene
 Diameter Tweeter 1" (25.4mm) silk dome aim-able
 Power Handling 125 watts (peak)
 Impedance 8 ohms (speaker) 5000 ohms @ 1 watt transformer
 Frequency Response 40Hz - 20kHz (± 10 dB)
 Dispersion 110°
 Sensitivity 92dB (1W 1M) Average

Transformers:

Wattage 10/20/30 watts 25 /70 volts
 Primary taps:
 E-675-TL-X 10, 5, 2.5, 1.25 watts
 E-675-TL-X20 20, 10, 5, 2.5 watts
 E-675-TL-X30 30, 15, 8, 4 watts
 Secondary tap 8 ohms
 Frequency response 40Hz – 15kHz (+/-5dB)
 Insertion loss 1.0dB

Included:

RI-675 rough-in bracket
 Cutout template
 Paint shield

Dimensions:

Dimensions Overall 9.125" (233mm)
 Cutout Dimensions Speaker 7.7" (196mm)
 Cutout Dimensions RI Bracket 8.1" (208mm)
 Depth 3- 1/4" (95.25mm)
 Shipping Weight 6.50 lbs (2.95kg)

