

Features:

- High power handling 6.5" in-ceiling speaker system
- New thin bezel magnetic grilles
- Smooth-wide frequency response
- 6.5 inch woven Kevlar woofer cone
- Rubber woofer surround
- 20oz ported ferrite woofer magnet
- 1 inch aim-able aluminum ceramic tweeter
- Neodymium tweeter magnet
- High quality crossover with air core inductors
- PTZ tweeter protection with automatic reset
- 6 heavy duty mounting clamps.
- 12awg binding posts
- Complete rough in brackets included (RI-K6IW)
- Paint able to match any decor

Sold as pairs
Master carton 3 pairs
10 year warranty



Specifications:

- Diameter Woofer 6.5" (165.1mm) woven Kevlar
- Diameter Tweeter 1" (25.4mm) aluminum ceramic aim-able
- Power Handling 125 watts (peak)
- Impedance 8 ohms (nominal)
- Frequency Response 40Hz - 20kHz (± 10 dB)
- Dispersion 110°
- Sensitivity 92dB (1W 1M) Average

Included:

- RI-K6IW rough-in brackets
- Cutout template

Dimensions:

Dimensions Overall

- Width 8.625" (218mm)
- Height 12" (306mm)
- Depth 3.25" (82.55mm)

Cutout Dimensions Speaker

- Width 7.375" (85mm)
- Height 10.75" (272mm)

Cutout Dimensions RI Bracket

- Width 7.75" (197mm)
- Height 11.125" (283mm)
- Shipping Weight 13 lbs (5.9kg)

Sold in pairs



Includes 2 x RI Brackets

