

#### Features:

High power handling 6.5" in-ceiling speaker system  
New trimless magnetic grille  
Smooth-wide frequency response  
6.5 inch woven Kevlar woofer cone  
Rubber woofer surround  
20 oz ferrite woofer magnet  
1 inch aim-able silk dome tweeter  
Neodymium tweeter magnet  
High quality crossover with air core inductors  
PTZ tweeter protection with automatic reset  
4 heavy duty "Tough-Cam" mounting clamps.  
Gold plated 12awg binding posts  
Complete rough in bracket included (RI-675)  
Paint able to match any decor  
Sold as pairs  
Master carton 2pcs  
10 year warranty



#### Specifications:

Diameter Woofer 6.5" (165.1mm) woven Kevlar  
Diameter Tweeter 1" (25.4mm) silk dome aim-able  
Power Handling 125 watts (peak)  
Impedance 8 ohms (nominal)  
Frequency Response 40Hz - 20kHz ( $\pm 10$ dB)  
Dispersion 110°  
Sensitivity 92dB (1W 1M) Average

#### Included:

RI-675 rough-in bracket  
Cutout template  
Paint shield

#### Dimensions:

Dimensions Overall 10.125" (250mm)  
Cutout Dimensions Speaker 8.25" (210mm)  
Cutout Dimensions RI Bracket 8.5" (216mm)  
Depth 3.5" (90mm)  
Shipping Weight 13lbs (5.9kg)  
Shipping dimensions 14x12x13"



New "Tough-Cam" Mounting System

