

Features:

In-wall microphone and line level pre-amplifier/mixer
 Locking Stainless Steel cover plate
 Fits most 2 gang electrical boxes
 Provides volume control of input sources
 Provides master volume control of-
 Factor Electronics amplifiers
 Two priority levels for momentary or continuous override
 Switchable 100Hz HPF, 15dB pad and phantom power
 Stereo RCA input automatically sums to mono
 Stereo 3.5mm input automatically sums to mono
 Locking balanced XLR/1/4" combo input jack
 Connects to Factor amplifiers with Cat5/6 wire
 Three VRVC-PRO units can be daisy chained-
 on a single Cat5/6 run
 All metal construction
 Removable front panel knobs
 Includes no-tamper security caps
 Includes 2 x RJ45 crimp-on connectors
 Includes 4 x white mounting screws
 Can be used with any amplifier or pre-amplifier with
 optional RVC-RJ45 Breakout adapter
 Three year warranty!



Specifications:

Frequency Response – 20Hz – 20kHz
 THD - <0.01%
 S/N ratio Microphone – 70dB
 S/N ratio Line – 80dB
 Mic input sensitivity - -50dB to +10dBu
 Line input sensitivity - -40dB to +14dBu
 Power requirements – 24vdc - 300mA
 (provided by Factor amps or V-RVC-RJ45 adapter)
 Vox sens adjustment - Yes

MIC Input:

100 Hz high pass filter switchable
 24vdc phantom power switchable
 15dB microphone pad switchable

Global:

RVC remote master volume control switchable

Mute:

Latching mute switch provides silent source connections

Priority:

Latching shorting switch requires
 2 additional wires connects to mute contacts on amplifier

Construction:

2 gang metal plate
 Fits 2 gang mud ring or
 2 gang metal or PVC back boxes

Front panel connections:

XLR/1/4" Combo balanced locking
 RCA Stereo – sums to mono
 3.5mm Stereo – sums to mono

Back panel connections:

RJ45 in
 RJ45 out

Includes:

2 x RJ45 connectors
 2 x Security keys
 4 x white mntg screws

Dimensions:

Width – 4.50" / 114.5mm
 Height – 4.54" / 115.5mm
 Depth – 1.75" / 44.4mm
 Weight – 2.2lb / 1.0kg

