

Features:

- High power handling 8" in-ceiling speaker system
- Trim-less magnetic grilles
- Smooth-wide frequency response
- 8 inch polypropylene woofer cone
- Rubber woofer surround
- 30 oz Ferrite woofer magnet
- 1 inch aim-able silk dome tweeter
- Neodymium tweeter magnet
- High quality crossover with air core inductor
- Pure white acoustically lined magnetic grille
- 4 heavy duty mounting clamps.
- Gold plated 12awg binding posts
- Rough in brackets included (RI-875)
- Available with 10, 20 or 30 watt 25/70 volt transformers
- Paint-able to match any decor
- Sold as pairs
- Master carton 2pcs
- 10 year warranty



Specifications:

- Diameter Woofer 8" (203.20mm) polypropylene
- Diameter Tweeter 1" (25.4mm) silk dome aim-able
- Power Handling 150 watts (peak)
- Impedance 8 ohms speaker 5000 ohms @ 1 watt transformer
- Frequency Response 35Hz - 20kHz (±10dB)
- Dispersion 110°
- Sensitivity 92dB (1W 1M) Average

Transformer:

- Wattage 10/20/30 watts
- 25 or 70 volts
- Four primary taps
- Secondary tap 8 ohms
- Frequency response 40Hz – 17kHz (+/-5dB)
- Insertion loss 1.0dB

Included:

- RI-875 rough-in brackets
- Cutout template
- Paint shield
- Installation manual

Dimensions:

- Dimensions Overall 10.875" (277mm)
- Cutout Dimensions Speaker 9.9" (250mm)
- Cutout Dimensions RI Bracket 10.125" (251mm)
- Depth 4.25" (107.95mm)
- Shipping Weight 18.lbs (7.25kg) per pair
- Shipping Weight master carton 1 pair 20Lbs



Optional Square Magnetic Grille
SG-K8-TL



Includes RI Brackets

