

# HDMI M/F VERTICAL RIGHT ANGLE (270°) ADAPTER

#### SKUS VA-HMHFD

#### **FEATURES**


- 270° HDMI Type A Female to HDMI Type A Male Vertical Right Angle Adapter 1 5/8" x 1 3/16" x 1/2"
- HDMI port saver for strain relief, preventing wear and tear on the HDMI port of your devices
- Vertical 270° right angle connector points away from the beveled side of the connector
- Provides exact angles for your applications, preventing bending of non-reversible HDMI cables
- Gold-plated connectors provide superior transmission, high reliability and durability
- All relevant materials are complied with RoHS directive






#### **AVAILABLE COLOUR**







## wiring diagram

<u>P1</u>	<u>P2</u>	<u>P1</u>	<u>P2</u>
1 ———	1	11	11
2 ———	2	12 ——	12
3 ———	3	13 ——	13
4 ———	<del>4</del>	14 ——	14
5 ———	5	15 ——	15
6 ———	<del></del> 6	16 ——	16
7 ———	<del></del> 7	17 ——	17
8 ———	8	18 ——	18
9 ———	——9	19 ——	19
10	10	SHELL -	SHELL

P1:HDMI A male P2:HDMI A female

#### **MATERIALS**

(1) HDMI A/F	Terminal: C2680 semi-gold TINGG/F; Shell: C2680/SPCC, Full gold/nickel; Rubber core: LCP; Sheath: Full wrap
(2) HDMI A/M	<b>Terminal:</b> C5191 semi-gold TING/F; <b>Shell:</b> C2680/SPCC, Full gold/nickel; <b>Rubber core:</b> LCP
(3) INTERNAL MODEL	High density PE
(4) EXTERNAL MODEL	45P black PVC
(5) PCB BOARD	ZS-12-P-020A

### **SPECIFICATIONS**

ROHS COMPLIANT   100% SHORT CIRCUIT BREAKING TEST		
TOLERANCE	.X ± .10   .XX ± .05   .XXX ± .03	
VOLTAGE RESISTANCE	300V DC (min.)	
CONTACT RESISTANCE	5 ohms (max.)	
INSULATION RESISTANCE	10M ohms (min.)	

© PC Cable World. All rights reserved.

PC Cable World product specifications are subject to change without notice, but are accurate at the time of printing. Please contact a sales representative for current specs. Please note that all physical specifications are nominal.