

RJ45 CAT6A 24-PORT PATCH PANEL (110 TYPE)

SKUS C6A-4524

FEATURES

- 1U 24-Port Loaded RJ45 Category 6A Patch Panel, with T568A/B colour coded wiring patterns
- Rack-mountable, fits within any standard 19" rack or cabinet
- Use with 110 punch-down tool with provided keystones for terminating 22-26 AWG Cat6A cable
- Labels on the front provide space for adding identification, with an additional port numbering system on the front and rear of the patch panel
- Meets ANS/TIA-568-C.2, IEEE802.3an for 10G BASE-T requirement, Third Party Tested, cETLus Intertek listed, and compliant with CISPR, FCC Class A, and RoHS
- Mounting hardware not included with patch panel

MATERIALS

FRONT PLATE	Fireproof ABS UL-94V0
PANEL	Metal (SPCC)
CABLE MANAGEMENT	Metal (SPCC)
JACK	8P8C 50 Micro-inches gold plated
PCB	FR-4 / UL-94V0
IDC BODY	Fireproof ABS UL-94V0
IDC PIN	Bronze & Tinned
IDC DESCRIPTION	For 22-26 AWG For 110 punch-down tool

SPECIFICATIONS

UL APPROVED 3P THIRD PARTY TESTED ROHS COMPLIANT	INSULATION RESISTANCE	500M ohms (min.)	
MEETS C6A EIA/TIA 568C STANDARD CETLUS CERTIFIED	CONTACT RESISTANCE	20m ohms (max.)	
IDC PUNCH DOWN CYCLE	Over 250 Cycles (min.)	CURRENT RATING	1.5 Amps
JACK INSERTION CYCLE	Over 2000 Cycles (min.)	DC RESISTANCE	0.1 ohms (max.)
OPERATION TEMPERATURE	-40 — +70 Degrees Celsius	WITHSTANDING VOLTAGE	1000 VAC RMS @ 60Hz/1min
TOLERANCE	X ± 1 .X ± 0.2 .XX ± 0.15		



AVAILABLE COLOURS



SIZE (WxDxH) 482 x 95.4 x 44 mm

