

RJ45 CAT5E 12-PORT LOADED PATCH PANEL (110 TYPE)

SKUS PP-4512

FEATURES

- 1U 12-Port Loaded RJ45 Category 5E Patch Panel, with T568A/B colour coded wiring patterns
- Rack-mountable, fits within any standard 19" rack or cabinet
- Use with 110 punch-down tool with keystones for terminating 22-26 AWG Cat5e cable
- Labels on the front provide space for adding identification, with an additional port numbering system on the front and rear of the patch panel
- Meets ANSI/EIA/TIA 568B AND ISO/IEC 11801 & EN50173 standards, RoHS compliant, Third Party Tested, and cETLus Intertek Listed
- Mounting hardware not included with patch panel

MATERIALS

| | |
|------------------------|--|
| FRONT PLATE | Fireproof ABS UL-94V0 |
| PANEL | Metal (SPCC) |
| JACK | 8P8C 50 Micro-inches gold plated |
| PCB | FR-4 / UL-94V0 |
| IDC CAP | Fireproof ABS UL-94V0 |
| IDC BODY | Fireproof ABS UL-94V0 |
| IDC PIN | Bronze & Tinned |
| IDC DESCRIPTION | For 22-26 AWG For 110 punch-down tool |

SPECIFICATIONS

| | | | |
|---|-------------------------------|-----------------------------|--------------------------|
| UL APPROVED 3P THIRD PARTY TESTED ROHS COMPLIANT | INSULATION RESISTANCE | 500M ohms (min.) | |
| MEETS C5E EIA/TIA 568A/B STANDARD CETLUS CERTIFIED | CONTACT RESISTANCE | 20m ohms (max.) | |
| IDC PUNCH DOWN CYCLE | Over 250 Cycles (min.) | CURRENT RATING | 1.5 Amps |
| JACK INSERTION CYCLE | Over 2000 Cycles (min.) | DC RESISTANCE | 0.1 ohms (max.) |
| OPERATION TEMPERATURE | -40 — +70 Degrees Celsius | WITHSTANDING VOLTAGE | 1000 VAC RMS @ 60Hz/1min |
| TOLERANCE | X ± 1 .X ± 0.2 .XX ± 0.15 | | |



AVAILABLE COLOURS



SIZE (WxDxH) 482 x 30 x 44 mm

