



# SC-SC MM DUPLEX 62.5/125 FIBER OPTIC CABLE

SKUS	SC-SC03	(3')	SC-SC25	(25')
	SC-SC06	(6')	SC-SC33	(33')
	SC-SC10	(10')	SC-SC50	(50')
	SC-SC15	(15')		



## FEATURES

- SCSC OM1 Multi-Mode Duplex Cable 62.5/125µm
- Use for transmitting gigabit data signals for telecommunications, such as local area networks or fiber to home applications
- Has low insertion loss, low back reflection loss, and isn't subjected to electromagnetic effects such as cross-talk or external interference
- Contains two fibers, supporting the flow of data in two directions
- Made with high quality Corning glass fiber core for durability and lower attenuation
- Robust snap-in Square Connectors (SC) are commonly found on media converters
- Premium grade ceramic ferrules with polished contacts to ensure optimal performance
- Environmentally stable, can be used in areas with volatile vapours



## MATERIALS

<b>(1) CONN A/B</b>	SC duplex conn/UPC
<b>(2) CABLE</b>	Coring optical fiber cable 62.5/125 MM OFNR (UL) MM/YY XXXXXM, Orange
<b>(3) MARKER RING 1</b>	L=3.7mm, <b>Colour:</b> White, <b>Print 1,</b> <b>Text colour:</b> Black
<b>(4) MARKER RING 2</b>	L=3.7mm, <b>Colour:</b> White, <b>Print 2,</b> <b>Text colour:</b> Black
<b>(5) H.S. TUBE</b>	Heat shrinking tube, Black, ID=3mm, L=10mm

## LENGTH TABLE

<b>3FT</b>	914±20mm	<b>25FT</b>	7620±50mm
<b>6FT</b>	1824±30mm	<b>33FT</b>	10032±100mm
<b>10FT</b>	3048±50mm	<b>50FT</b>	15240±100mm
<b>15FT</b>	4572±50mm		

## SPECIFICATIONS

<b>TIA/EIA-568B.3   BELLCORE GR-020   UL OFNR/FT4 STANDARD</b>	<b>INSERTION LOSS</b>	≤ 0.3 dB	
<b>OPERATION TEMPERATURE</b>	-20 — +70 Degrees Celsius	<b>RETURN LOSS</b>	≥ 35 dB
<b>STORAGE TEMPERATURE</b>	-40 — +70 Degrees Celsius	<b>MINI BENDING RADIUS</b>	6cm (Loaded) 3cm (Unloaded)
<b>TOLERANCE</b>	.X ± 0.3   .XX ± 0.1   .XXX ± 0.05		

© PC Cable World. All rights reserved.

PC Cable World product specifications are subject to change without notice, but are accurate at the time of printing. Please contact a sales representative for current specs. Please note that all physical specifications are nominal.