

Features:

Hi fidelity 4.5" surface mount speaker system (PAIR)
Suitable for indoor or outdoor use
IP66 dirt/dust/moisture rated
Smooth-wide frequency response
Excellent fidelity for music or voice
4.5" **Graphite** woofer cone
Rubber woofer surround
12oz ported Ferrite woofer magnet
1 inch **titanium** dome tweeter
Neodymium tweeter magnet
PTZ tweeter protection with auto reset
High quality crossover with air core inductor
Aluminum non-rusting grille
Multi-position pivoting aluminum mounting brackets
Mounts vertically or horizontally
Gold plated 12awg binding posts
Includes internal 30watt 25/70 volt transformer
Transformer includes 8 ohm bypass setting
Sold as pairs
Master carton 1 pair
1 year warranty



Specifications:

IP66 rated (dust/dirt/powerful jet water resistant)
Diameter Woofer 4.5" (115mm) graphite
Diameter Tweeter 1" (25.4mm) titanium
Power Handling 80watts RMS
Impedance 8 ohms (nominal)
Frequency Response 75Hz - 20kHz (± 5 dB)
Dispersion 110°
Sensitivity 86dB (1W 1M) Average
Grille/Bracket material Aluminum
Color Black



Horizontal or vertical mounting

Included:

Internal Transformer 30 watts 25/70 volt
Wattage taps 30w, 15w, 7.5w, 3.75w & 8ohms
Pivoting powder coated aluminum mounting brackets x 2

Dimensions:

Dimensions Overall
Height 9.05" (230mm)
Width 6.10" (155mm)
Depth 5.82" (148mm) including bracket
Shipping Weight 13.2lbs (6kg) per pair



Sealed IP66 Connections