


DESCRIPTION

18/2 Stranded Bare Copper Conductors, Unshielded with an overall jacket. Plenum Rated, 1000ft Pull Box

FEATURES

- Intercom Systems
- Security Systems
- Sound and Audio
- Power Limited Control Circuits
- Indoor Applications
- Supplied in a 1000ft Pull Box



18AWG 2 CONDUCTORPLENUM RATED

SKU: 211-182/P/WH

Conductor

Material Bare Copper Size 18AWG

Stranding 7 Strand (7x.0152in., 7x.386mm)

Conductors 2 Conductor

Insulation

Material PL-PVC

Thickness 0.06 in. (1.52mm) Nominal

Colors Black, Red

Ripcord Yes

Jacket

Material PL-PVC

Thickness 0.0181 in. (0.46mm) Nominal Overall Diameter 0.157 in. (4.00mm) Nominal

Color White

Electrical Properties

Temp. Rating $-20^{\circ}\text{C} \sim +75^{\circ}\text{C}$

DCR Conductor 21.9 Ohms/Km. @ 20°C

Ratings/Approvals

NEC Article 800, UL Subject 444, CMP/CL2P (UL), RoHS Compliant







VERTICAL CABLE

951.696.7772 California 800.749.2447 Florida 845.391.8318 New York