

ES-7832-P16

32CH 16 PoE Network Video Recorder




Key Features

- Up to 32 Ch. IP cameras input
- 256 Mbps Input Max and 256 Mbps Output Max
- Support H.265
- Up to 12 MP resolution recording
- Independent VGA output up to 1080p, HDMI output at up to 4K resolution
- Plug & Play with 16 independent PoE network interfaces
- Support POS function



Physical Interfaces



Model Number

ES-7832-P16

Video Compression	H.264 / H.264 / H.265
IP Video Input	32 Ch. (256 Mbps Max input)
Video Output	1 HDMI, 1 VGA, 1 BNC
Audio Input/Output	1/1
Two-way Audio	1/1
Real-time recording resolution	Up to 12 Megapixels
HDMI Output Resolution	4K
VGA Output Resolution	1080P, 60Hz
RAID	N/A
Synchronous Playback	4 Ch. @ 4K, or 16 Ch. @ 1080P
Alarm Input/ Output	16/4
Network Interface	1 RJ45 10M/100M/1000M adaptive Ethernet Interface
PoE Network Interfaces/Built-in switch	16 independent 100 Mbps PoE network interfaces
Internal SATA	4 SATA interfaces (up to 8TB each)
eSATA	1 eSATA
USB interface	2 x USB2.0, 1 x USB3.0
Chassis	19-inch rack-mounted 1.5U
Dimensions (W × D × H)	17.5"W × 15.4"D × 2.75"H
Power Supply	100 ~ 240 VAC, 20W
Weight	11 lbs (without hard disk)