

# RJ45 CAT6 WHITE SURFACE-MOUNT COUPLER (TOOL-LESS)

**SKUS** C6-669W

## FEATURES

- Tool-Less White RJ45 Cat6 Surface-Mount In-Line Coupler 48 x 24.7 x 25.8 mm
- Use to directly connect two RJ45 Cat6 cables and mount on the exterior side of a wall
- Use with 110 punch-down tool or IDC cap for tool-less terminations
- For use with 22-26 AWG Cat6 cable, recommended for use with solid conductor cable
- Easy open and close snap cover for accessing keystones
- Includes two cable ties for strain relief, and a screw to close the assembly
- Wall-Mounting hardware is not included

## MATERIALS

<b>BODY</b>	Fireproof ABS UL-94V0
<b>PCB</b>	FR-4 / UL-94V0
<b>IDC CAP</b>	Fireproof PC + Glass Fiber UL-94V2
<b>IDC BODY</b>	Fireproof ABS UL-94V0
<b>IDC PIN</b>	Phosphor Bronze & Tinned
<b>IDC DESCRIPTION</b>	For 22-26 AWG For 110 punch-down Tool Tool-less (when use IDC cap directly)

## SPECIFICATIONS

<b>UL APPROVED   3P THIRD PARTY TESTED   ROHS COMPLIANT</b>	<b>INSULATION RESISTANCE</b>	500M ohms (min.)	
<b>MEETS C6 EIA/TIA 568B STANDARD   CETLUS CERTIFIED</b>	<b>CONTACT RESISTANCE</b>	20m ohms (max.)	
<b>IDC PUNCH DOWN CYCLE</b>	Over 250 Cycles (min.)	<b>CURRENT RATING</b>	1.5 Amps
<b>OPERATION TEMPERATURE</b>	-40 — +70 Degrees Celsius	<b>DC RESISTANCE</b>	0.1 ohms (max.)
<b>TOLERANCE</b>	X ± 1   .X ± 0.2   .XX ± 0.15	<b>WITHSTANDING VOLTAGE</b>	1000 VAC RMS @ 60Hz/1min

© PC Cable World. All rights reserved.

PC Cable World product specifications are subject to change without notice, but are accurate at the time of printing. Please contact a sales representative for current specs. Please note that all physical specifications are nominal.

[www.pccableworld.com](http://www.pccableworld.com)



## AVAILABLE COLOURS



**SIZE (WxDxH)** 48 x 24.7 x 25.8 mm

