

RJ45 CAT6A SLIM BLUE KEYSTONE JACK (TOOL-LESS)

SKUS

- C6-A69BK (Black)
- C6-A69BL (Blue)
- C6-A69WT (White)

FEATURES

- Category 6A RJ45 UTP Slim Keystone (8P8C) 16.6 x 36.5 x 22.3 mm
- Use with 10 Gigabit network applications to terminate 22-26 AWG Cat6A stranded or solid cable
- No tool required, can use 110 punch-down tool or plastic IDC cap for tool-less terminations
- Snap in for use with standard sized wall plates, surface-mount boxes, or unloaded patch panels
- 90° wire connection
- Compatible and labelled with both 568A and 568B wiring color codes
- PCB technology provides maximum performance and superior signal quality
- Fireproof ABS UL-94V0 body
- 3P Third Party Tested, meets or exceeds C6A EIA/TIA 568C standards, ETL Intertek listed
- Backward compatible with previous ethernet categories

MATERIALS

BODY	Fireproof ABS UL-94V0
JACK	8P8C 50 Micro-inches gold plated
PCB	FR-4 / UL-94V0
IDC CAP	Fireproof ABS UL-94V0
IDC BODY	Fireproof ABS UL-94V0
IDC PIN	Phosphor Bronze & Tinned
IDC DESCRIPTION	For 22-26 AWG For 110 punch-down Tool Toolless (when use IDC cap directly)

SPECIFICATIONS

UL APPROVED 3P THIRD PARTY TESTED ROHS COMPLIANT	INSULATION RESISTANCE	500M ohms (min.)	
MEETS C6A EIA/TIA 568C STANDARD CETLUS CERTIFIED	CONTACT RESISTANCE	20m ohms (max.)	
IDC PUNCH DOWN CYCLE	Over 250 Cycles (min.)	CURRENT RATING	1.5 Amps
JACK INSERTION CYCLE	Over 2000 Cycles (min.)	DC RESISTANCE	0.1 ohms (max.)
OPERATION TEMPERATURE	-40 – +70 Degrees Celsius	WITHSTANDING VOLTAGE	1000 VAC RMS @ 60Hz/1min
TOLERANCE	X ± 1 .X ± 0.2 .XX ± 0.15		

© PC Cable World. All rights reserved.

PC Cable World product specifications are subject to change without notice, but are accurate at the time of printing. Please contact a sales representative for current specs. Please note that all physical specifications are nominal.

www.pccableworld.com



AVAILABLE COLOURS



SIZE (WxDxH) 16.6 x 36.5 x 22.3 mm

